

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- **1.1 Product identifier**
- **Trade name:** **PRENOFIX 100/00**
- **Article number:** 110908.0162.TV
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Product category** PC1 Adhesives, sealants
- **Application of the substance / the mixture** Adhesives
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
EURO-LEDER
Werner-von-Siemens-Str. 35 a
D – 49124 Georgsmarienhütte
Tel.: ++49 (0) 5401/88081-0
Mail: info@euro-service-depot.de
- **Informing department:** Regulatory department
- **1.4 Emergency telephone number:**
NCEC emergency service
+44 (0) 1235 239 670 (24 hours)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Repr. 2 H361d Suspected of damaging the unborn child.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08 GHS09

- **Signal word** Danger
- **Hazard-determining components of labelling:**
toluene
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 1)

- **Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

Contains Rosin, Rosin. May produce an allergic reaction.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:**

Adhesive.
Polychloroprene

- **Dangerous components:**

Note P of Annex 1 applies to the components (*) of this product. ratio of Benzen < 0,1 % in weight.

CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-0000	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (*) Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-0000	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (*) Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-0000	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
EC number: 931-254-9 Reg.nr.: 01-2119484651-34	Hydrocarbons, C6, isoalkanes, <5% n-hexane (*) Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 79-20-9 EINECS: 201-185-2	methyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	5-10%
CAS: 110-82-7 EINECS: 203-806-2 Reg.nr.: 01-2119486291-36-0000	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	<2.5%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 2)

CAS: 110-54-3 EINECS: 203-777-6	<i>n</i> -hexane Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	0.5-1%
CAS: 8052-10-6 EINECS: 232-484-6	Rosin Skin Sens. 1, H317	< 0.5%
CAS: 8050-09-7 EINECS: 232-475-7 Reg.nr.: 01-2119480418-32-0000	Rosin Skin Sens. 1, H317	< 0.2%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information**
Instantly remove any clothing soiled by the product.
Take affected persons into the open air.
- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact**
Instantly wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.
- **After swallowing** Do not induce vomiting; instantly call for medical help.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
CO₂, sand, extinguishing powder. Do not use water.
Use fire fighting measures that suit the environment.
Water haze
Foam
Fire-extinguishing powder
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**
Can be released in case of fire
Carbon monoxide (CO)
Hydrogen chloride (HCl)
Carbon monoxide and carbon dioxide
Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered containers with water spray jet.
Collect contaminated fire fighting water separately. It must not enter drains.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 3)

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Wear protective clothing.
- **6.2 Environmental precautions:**
Do not allow to enter drainage system, surface or ground water.
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Send for recovery or disposal in suitable containers.
Do not use tools that can cause ignition.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Store in cool, dry place in tightly closed containers.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Take note of emission threshold.
Use solvent-proof equipment.
Keep out of the reach of children.
- **Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.
Highly volatile, flammable constituents are released during processing.
Fumes can combine with air to form an explosive mixture.
Flammable mixtures may be formed in empty containers.

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Provide solvent resistant, sealed floor.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Protect from heat and direct sunlight.
Store in cool, dry conditions in original sealed container
- **Recommended storage temperature:** +10°C - +25°C

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 4)

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **8.1 Control parameters**

- **Components with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate

WEL	Short-term value: 400 ppm Long-term value: 200 ppm
-----	---

108-88-3 toluene

WEL	Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk
-----	--

79-20-9 methyl acetate

WEL	Short-term value: 770 mg/m ³ , 250 ppm Long-term value: 616 mg/m ³ , 200 ppm
-----	---

- **DNELs**

Ethylacetat, CAS 141-78-6 (Arbeitnehmer)
 dermal Langzeit(chronisch) systemisch: 63 mg/kg/Tag
 inhalativ Kurzzeit (akut) systemisch: 1468 mg/m³
 inhalativ Langzeit(chronisch) lokal: 734 mg/m³
 inhalativ Kurzzeit (akut) lokal: 1468 mg/m³
 inhalativ Langzeit (chronisch) systemisch: 734mg/m³
 Toluol CAS 108-88-3
 Inhalation Kurzzeit – lokale Auswirkungen Arbeiter 343 mg/m³
 Inhalation Kurzzeit – systemische Auswirkungen Arbeiter 384 mg/m³
 Inhalation Langzeit – lokale Auswirkungen Arbeiter 192 mg/m³
 Inhalation Langzeit – systemische Auswirkungen Arbeiter 192 mg/m³
 Dermal Langzeit – systemische Auswirkungen Arbeiter 384 mg/kg
 Cyclohexan CAS 110-82-7

DNEL-Werte

Akute Wirkungen - systemische Effekte, inhalativ: 700 mg/m³
 Chronische Wirkungen - systemische Effekte, inhalativ: 700 mg/m³
 Chronische Wirkungen - systemische Effekte, dermal: 2016 mg/kg

- **PNECs**

Ethylacetat 141-78-6
 Wasser Süßwasser: 0,26 mg/l
 Wasser Meerwasser: 0,026 mg/l
 Wasser Aqua intermittent: 1,65 mg/l
 Wasser Süßwasser Sediment: 1,25 mg/kg
 Wasser Meerwasser Sediment: 0,125 mg/kg
 Boden - 0,24 mg/kg
 Kläranlage (STP) - 650 mg/l
 Sekundärvergiftung - 200 mg/kg

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 5)

Toluol CAS 108-88-3
 Süßwasser 0,68 mg/l
 Sediment (Süßwasser) 16,39 mg/kg
 Boden 2,89 mg/kg
 Kläranlage (STP) 13,61 mg/l
 Cyclohexan CAS 110-82-7
 PNEC 2,99 mg/kg (Boden)
 3,24 mg/l (Kläranlagen)
 0,207 mg/l (Meerwasser)
 3,627 mg/kg (Süßwassersediment)
 0,207 mg/l (Süßwasser)
 0,207 mg/l (sporadische Freisetzung)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

The usual precautionary measures should be adhered to general rules for handling chemicals.

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Use breathing protection in case of insufficient ventilation.

· **Recommended filter device for short term use:** Combination filter A-P2

· **Protection of hands:**



Protective gloves.

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR

· **Penetration time of glove material**

The information is based on literature data and information of glove manufacturers.

Value for the permeation: Level ≤ 4

· **Eye protection:**



Tightly sealed safety glasses.

· **Body protection:** Protective work clothing.

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	Ember coloured
Odour:	Characteristic
Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	57 °C (DIN 53171)

· Flash point: -26 °C (DIN 53213)

· Inflammability (solid, gaseous) Not applicable.

· Decomposition temperature: Not determined.

· Self-inflammability: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/steam mixtures is possible.

· Critical values for explosion:

Lower:	0.6 Vol % (EN 1839)
Upper:	16.0 Vol % (EN 1839)

· Vapour pressure at 20 °C: 220 hPa (DIN 51640)

· Density at 20 °C ca. 0.85 g/cm³ (DIN 51757)

· Relative density Not determined.

· Vapour density Not determined.

· Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

dynamic at 20 °C:	ca. 1100 mPas (Brookfield (ISO 2555))
kinematic:	Not determined.

· Solvent content:

Organic solvents: ca. 81 %

Solids content: ca. 19 % (ISO 3251)

· 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with alcohols, amines, aqueous acids and alkalis

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 7)

- Develops readily flammable gases / fumes
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5,800 mg/kg (rat)
Dermal	LD50	>2,900 mg/kg (rat)
Inhalative	LC50/4h	33 mg/l (rat)

141-78-6 ethyl acetate

Oral	LD50	5,620 mg/kg (rat)
Inhalative	LC50/4h	22.5 mg/l (rat)

108-88-3 toluene

Oral	LD50	5,001 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rab)
Inhalative	LC50/4h	49 mg/l (rat)

79-20-9 methyl acetate

Oral	LD50	6,970 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

Hydrocarbons, C6 isoalkanes, <5% n-hexane

Oral	LD50	>5,800 mg/kg (rat)
Dermal	LD50	>2,900 mg/kg (rat)
Inhalative	LC50/4h	33 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 8)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

141-78-6 ethyl acetate

LC50/96h	230 mg/l (<i>Pimephales promelas</i>)
IC50/48h	3,300 mg/l (<i>Desmodesmus subspicatus</i>)
EC50/48h	717 mg/l (<i>Daphnia magna</i>)

108-88-3 toluene

LC50/96h	36.2 mg/l (<i>Pimephales promelas</i>)
	13 mg/l (<i>Carassius auratus</i>)
IC50/72h	12 mg/l (<i>Selenastrum capricornutum</i>)
EC50/48h	11.5 mg/l (<i>Daphnia magna</i>)

79-20-9 methyl acetate

LC50/96h	250-350 mg/l (<i>Brachydanio rerio</i>)
EC50/48h	1,027 mg/l (<i>Daphnia magna</i>)

12.2 Persistence and degradability

141-78-6 ethyl acetate

Bio.Abbaubark./28 d	100 % (-)
---------------------	-----------

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated under adherence to official regulations.

European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018




Trade name: PRENOFIX 100/00

(Contd. of page 9)

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA 	UN1133
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA 	1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS ADHESIVES (HEPTANES, Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane (*)), MARINE POLLUTANT ADHESIVES
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG 	<div style="display: flex; align-items: center; gap: 10px;">   </div> <p>· Class · Label</p> <p>3 Flammable liquids. 3</p>
<ul style="list-style-type: none"> · IATA 	<div style="display: flex; align-items: center; gap: 10px;">  </div> <p>· Class · Label</p> <p>3 Flammable liquids. 3</p>
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	III
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): 	Product contains environmentally hazardous substances: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (*) Yes Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category 	Warning: Flammable liquids. 33 F-E,S-D A
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 10)

· **Transport/Additional information:**

- | | |
|---|--|
| <ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ)
 · Transport category · Tunnel restriction code · Remarks: | <p>5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml</p> <p>3
D/E
Viscous according to ADR § 2.2.3.1.4 (Packaging group III when packed in receptacles not exceeding 450 L capacity)</p> |
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ)
 · Remarks: | <p>5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml</p> <p>Viscous according to 2.3.2.2 of the IMDG code (Packaging group III when packed in receptacles not exceeding 30 L capacity)</p> |
| <ul style="list-style-type: none"> · IATA · Remarks: | <p>Viscous according to IATA § 3.3.3.1 (Packaging group III when packed in receptacles not exceeding 30 L capacity)</p> |
| <ul style="list-style-type: none"> · UN "Model Regulation": | <p>UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY HAZARDOUS</p> |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
 - **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 48
 - **National regulations**
 - **Technical instructions (air):**
- | Class | Share in % |
|-------|------------|
| NK | 50-100 |
- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
 - **VOC (EU) %** 80.58 %
 - **Code MAL** 5-3
 - **VOC (EU)** 685.0 g/l
 - **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

GB

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: **PRENOFIX 100/00**

(Contd. of page 11)

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

- **Department issuing data specification sheet:** Regulatory department

- **Contact:** EU-MSDS@hbfuller.com

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Repr. 2: Reproductive toxicity – Category 2
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

- *** Data compared to the previous version altered.**

GB

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 12)

Annex: Exposure scenario 1

- **Short title of the exposure scenario**
ETHYL ACETATE (CAS141-78-6)
INDURSTRIL USE IN RIGID FOAM, COATINGS, ADHESIVES AND SEALANTS
- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC1 Adhesives, sealants
- **Process category**
PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC5 Mixing or blending in batch processes
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC10 Roller application or brushing
PROC13 Treatment of articles by dipping and pouring
- **Environmental release category**
ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use** Customary application according to section 1.
- **Duration and frequency**
8hrs (full working shift).
5 workdays/week.
- **Physical parameters**
- **Physical state** Liquid
- **Concentration of the substance in the mixture** The substance is main component.
- **Used amount per time or activity** 5500 tons per year
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
Avoid contact with the skin and eyes.
Take precautionary measures against static discharge.
Keep away from sources of ignition - No smoking.
- **Other operational conditions affecting consumer exposure** Keep out of the reach of children.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
Ensure adequate ventilation
Do not inhale gases / fumes / aerosols.
- **Organisational protective measures** Keep good industrial hygiene.
- **Technical protective measures**
Provide explosion-proof electrical equipment.
Keep containers tightly sealed.
Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Protective work clothing.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Tightly sealed safety glasses.
Protective gloves.

(Contd. on page 14)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 13)

- **Measures for consumer protection**
Ensure adequate labelling.
Keep locked up and out of the reach of children.
- **Environmental protection measures**
- **Water** *No special measures required.*
- **Disposal measures** *Ensure that waste is collected and contained.*
- **Disposal procedures**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Waste type** *Partially emptied and uncleaned packaging*
- **Exposure estimation**
- **Worker (dermal)** *The calculated value is smaller than the DNEL.*
- **Worker (inhalation)** *The calculated value is smaller than the DNEL.*
- **Environment** *The calculated value is smaller than the PNEC.*
- **Consumer** *Not relevant for this Exposure Scenario.*
- **Guidance for downstream users**
Whether the downstream user uses the substance / the mixture within the scope of the Exposure Scenario can be determined by means of a technical assessment.

GB

(Contd. on page 15)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 14)

Annex: Exposure scenario 2

- **Short title of the exposure scenario**

TOLUENE (CAS 108-88-3)

Industrielle Verwendung von Beschichtungen und Klebstoffen

- **Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

- **Product category** PC1 Adhesives, sealants

- **Process category**

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC5 Mixing or blending in batch processes

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC14 Tableting, compression, extrusion, pelletisation, granulation

PROC15 Use as laboratory reagent

- **Environmental release category**

ERC2 Formulation into mixture

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

- **Description of the activities / processes covered in the Exposure Scenario**

See full text of the descriptors in section 1.

- **Conditions of use** Customary application according to section 1.

- **Duration and frequency** 5 workdays/week.

- **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- **Physical state** Fluid

- **Concentration of the substance in the mixture** Raw material.

- **Other operational conditions** Observe the normal safety regulations when handling chemicals

- **Other operational conditions affecting environmental exposure**

Observe section 6 of the Safety Data Sheet (Accidental release measures).

- **Other operational conditions affecting worker exposure**

Do not breathe gas/fume/vapour/aerosol.

Avoid contact with the skin and eyes.

Keep away from food, drink and animal feedingstuffs.

Keep away from sources of ignition - No smoking.

- **Risk management measures**

- **Worker protection**

- **Organisational protective measures** No special measures required.

- **Technical protective measures** Ensure that suitable extractors are available on processing machines

- **Personal protective measures**

The usual precautionary measures should be adhered to general rules for handling chemicals.

- **Exposure estimation**

- **Consumer** Not relevant for this Exposure Scenario.

GB

(Contd. on page 16)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 2

Revision: 16.03.2018

Trade name: PRENOFIX 100/00

(Contd. of page 15)

Annex: Exposure scenario 3

- **Short title of the exposure scenario**

Cyclohexane

Industrielle Verwendung von Beschichtungen und Klebstoffen

- **Sector of Use** SU3 *Industrial uses: Uses of substances as such or in preparations at industrial sites*

- **Product category** PC1 *Adhesives, sealants*

- **Process category**

PROC1 *Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.*

PROC2 *Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions*

PROC3 *Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition*

PROC4 *Chemical production where opportunity for exposure arises*

PROC5 *Mixing or blending in batch processes*

PROC8a *Transfer of substance or mixture (charging and discharging) at non-dedicated facilities*

PROC8b *Transfer of substance or mixture (charging and discharging) at dedicated facilities*

PROC9 *Transfer of substance or mixture into small containers (dedicated filling line, including weighing)*

PROC15 *Use as laboratory reagent*

- **Environmental release category** ERC3 *Formulation into solid matrix*

- **Notes** *The product is intended for professional use.*

- **Description of the activities / processes covered in the Exposure Scenario**

See Section 1 of the Safety Data Sheet

- **Conditions of use** *Customary application according to section 1.*

- **Duration and frequency** *5 workdays/week.*

- **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- **Physical state** *Fluid*

- **Concentration of the substance in the mixture** *Raw material.*

- **Other operational conditions** *Observe the normal safety regulations when handling chemicals*

- **Other operational conditions affecting environmental exposure**

Observe section 6 of the Safety Data Sheet (Accidental release measures).

- **Other operational conditions affecting worker exposure** *Avoid contact with the skin and eyes.*

- **Other operational conditions affecting consumer exposure** *No special measures required.*

- **Risk management measures**

- **Worker protection**

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Technical protective measures** *Ensure good ventilation/exhaustion at the workplace.*

- **Personal protective measures**

The usual precautionary measures should be adhered to general rules for handling chemicals.

- **Environmental protection measures**

Avoid release to the environment. Obtain special instructions / refer to Safety Data Sheet.

- **Disposal measures**

Must not be disposed of with household waste. Do not allow to reach sewage system.

- **Disposal procedures**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Waste type** *Partially emptied and uncleaned packaging*

- **Exposure estimation**

- **Consumer** *Not relevant for this Exposure Scenario.*