

Safety Data Sheet dated 1/7/2014, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification: GALA VELOUR FRESH 8987

Trade name: RENOVATEUR DAIM

Trade code: ZPFI4111211A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Shoe care product.

1.3. Details of the supplier of the safety data sheet

EURO-LEDER GmbH & Co. KG Werner-von-Siemens-Str. 35a D-49124 Georgsmarienhütte

www.euroleder.de

Competent person responsible for the safety data sheet:

Tel: ++49 (0) 5401/880 81-0

Fax: ++49 (0) 5401/880 81-35 (Mo-Tu 8.00-17.00; Fr 8.00-16.00)

e-mail: info@euro-service-depot.de

1.4. Emergency telephone number

Giftinformationszentrum-Nord (GIZ), Göttingen, ++49 (0) 551/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Directive criteria, 67/548/CE, 99/45/EC and following amendments thereof:

Properties / Symbols:

This product is not a hazardous article and need not be labelled according to EC Directive 67/548, 99/45 as amended.

EC regulation criteria 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Symbols:

None

Hazard statements:

None

Precautionary statements:

None

Special Provisions:

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None



Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

>= 7% - < 10% 1-METHOXY-2-PROPANOL

Index number: 603-064-00-3, CAS: 107-98-2, EC: 203-539-1

R10-67

2.6/3 Flam. Liq. 3 H226

3.8/3 STOT SE 3 H336

>= 3% - < 5% Black colorant

R10-52/53

2.6/3 Flam. Liq. 3 H226

4.1/C3 Aquatic Chronic 3 H412

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters



Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhaltion of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No occupational exposure limit available

DNEL Exposure Limit Values

1-METHOXY-2-PROPANOL - CAS: 107-98-2

Worker Industry: 369 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term,

systemic effects

Worker Industry: 553.5 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term,

local effects

Worker Industry: 50.6 mg/kg - Exposure: Human Dermal - Frequency: Short Term,

systemic effects

PNEC Exposure Limit Values

1-METHOXY-2-PROPANOL - CAS: 107-98-2

Target: Fresh Water - Value: 10 mg/l

Target: Marine water - Value: 1 mg/l

Target: Freshwater sediments - Value: 41.6 mg/kg Target: Marine water sediments - Value: 4.17 mg/kg

Target: Soil (agricultural) - Value: 100 mg/l

8.2. Exposure controls

Eve protection:



Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

Environmental exposure controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance and colour:

Odour:

N.A.

Odour threshold:

PH:

Melting point / freezing point:

Initial boiling point and boiling range:

Solid/gas flammability:

N.A.

Liquide

N.A.

N.A.

N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A. Flash point: N.A. Evaporation rate: N.A. Vapour pressure: N.A. 0,90-1,00 Relative density: Solubility in water: Soluble Solubility in oil: N.A. Partition coefficient (n-octanol/water): N.A. Auto-ignition temperature: N.A. N.A.

Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Viscosity: N.A.
Explosive properties: N.A.
Oxidizing properties: N.A.

9.2. Other information

Miscibility: N.A. Fat Solubility: N.A. Conductivity: N.A.

N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.



SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

1-METHOXY-2-PROPANOL - CAS: 107-98-2

h) STOT-single exposure:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

SELLA DERM BLACK M2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2 mg/kg

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure:
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

NΑ

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

14.2. UN proper shipping name

ADR-Shipping Name:

IATA-Shipping Name:

ENTER PROPER SHIPPING NAME

ENTER PROPER SHIPPING NAME

ENTER PROPER SHIPPING NAME



- 14.3. Transport hazard class(es)
- 14.4. Packing group
- 14.5. Environmental hazards
- 14.6. Special precautions for user
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)

Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Dir. 2006/8/EC

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 453/2010 (Annex I)

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.00

Where applicable, refer to the following regulatory provisions:

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of phrases referred to in Section 3:

R10 Flammable.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.



It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LTE: Long-term exposure.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STE: Short-term exposure.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day.

(ACGIH Standard).

WGK: German Water Hazard Class.